



**BEXT**  
**XL 6000**

## Ultra Compact 6000 W Full Featured FM Transmitter

- Easy access to settings, functions and readings via touch screen color display and via web page
- Built-in User Manual file always accessible via front panel port even when AC power is disconnected
- Options include AES-EBU Digital Audio Input, Dynamic RDS/RBDS Encoder, Audio Over IP, SNMP2
- Newest high efficiency, high ruggedness LD MOS devices capable of withstanding 65:1 VSWR
- Conservatively rated, easily replaceable, highly efficient power supplies
- Proportional Auto-Foldback of RF output power protection in the event of excessive VSWR
- Excellent audio performance and built-in Stereo Generator with fast acting audio limiter
- Up to six available user-programmable profile presets for use as a backup of multiple FM stations
- Programmable FSK ID Keyer by software for use as auto-ID of Translators or Boosters
- Optional 10 MHz Ext Ref port + 1 pps port for Phase Locking & Time Delay Adj. to sync boosters or SFNs
- Highly efficient transmitters with low power consumption and low heat generation
- All Bext FM transmitters include low pass/harmonic filter and meet or exceed all FCC requirements

### ● RF Specifications

**Nominal RF Output Power:** 6000 W  
adjustable from menu or via webpage  
**Power control stability:** Better than 0.1 dB  
**RF Output:** 1 5/8" EIA Flange (or 7/8" EIA Flange on request) 50  $\Omega$  unbalanced.  
**Frequency range:** 87.5-108 MHz, front panel programmable or via webpage, 10 kHz steps  
**Reference:** 10 MHz TCXO  
**Off-lock attenuation:** > 80 dBc  
**Start-up time:** Typically 5-10 seconds  
**Type of modulation:**  
F3E / F8E direct FM at carrier frequency  
**Frequency deviation:** Nominal  $\pm 75$  kHz,  
**Accuracy of deviation:**  
<  $\pm 2$  dB from 87.6 to 107.9 MHz  
**Frequency drift:**  $\leq 1$  kHz/year MAX (due to internal TCXO aging).  
**Short term stability:**  $\pm 1$  ppm from -5 to +45  $^{\circ}$ C (100 Hz @ 100 MHz)  
**RF Harmonics:**  
Exceeds EBU/CCIR/FCC requirements  
**RF Spurious:**  
Exceeds EBU/ CCIR/FCC requirements

### ● Audio General Specs

**Preemphasis:** Selectable Flat / 50 / 75 micros.  
**Preemphasis Precision:** Better than  $\pm 0.5$  dB  
**Wideband Amplitude Response:**  
 $\pm 0.2$  dB 30 Hz to 100 kHz  
**Wideband AM Asynchronous:** (FM = no modulation, Ref = 100 % AM, Unweighted, RMS detector, BW 30-100 kHz) < -68dB, typ. -80dB  
**Wideband Distortion, THD:** < 0.1% (typ. 0.05%)  
**WB Distortion, IMD:** < 0.1% (typ. 0.05%)  
**WB Transient IMD:** < 0.25% (square/sine wave)

### ● Composite & Mono Specs

**S/N:** Typical Values referred to  $\pm 75$  kHz:  
Weighted (CCIR 468/2 - Peak CCIR detector)  
- 75 dB / 50  $\mu$ s - 69 dB / flat;  
Weighted (CCIR 468/2 - RMS detector) - 79 dB / 50  $\mu$ s - 72 dB / flat;  
Unweighted (RMS detector, meas. 20 Hz-23 kHz) - 86 dB / 50  $\mu$ s - 80 dB / flat (stereo);

Unweighted (RMS detector, meas. 20 Hz-23 kHz) - 92 dB / 50  $\mu$ s - 88 dB / flat (mono)  
**IMD:** 70 Hz / 6 kHz 4:1 RATIO < 0.03% measured with 1 kHz and 1.3 kHz tones, 1:1 ratio @ 75 kHz deviation  
**Transient IM:** < 0.03 % (square/sine)  
**Audio response:**  $\pm 0.15$  dB 20 Hz to 15 kHz  
**AM Synchronous:** (AM = 400 Hz, FM = 400 Hz  $\pm 75$  kHz Ref. = 100 % AM, RMS detector, meas. 20 Hz-23 kHz) < -69 dB  
**AM Asynchronous:** FM = no modulation, Ref. = 100 % AM, Unweighted, RMS detector, meas. 20Hz-23kHz) < -70 dB (typ. -85 dB)  
**Common mode rejection:** > 45 dB typical, 25 Hz to 15 kHz

### ● Built-in Stereo Gen. Specs

**Stereo System:** EBU/CCIR/FCC standard "Pilot Tone System"  
**Pilot Tone Frequency:** 19 kHz  $\pm 1$  Hz  
**Pilot Tone Deviation:**  $\pm 7$  kHz nominal  
**38 kHz Suppression:** > 70 dB (typ. 85 dB)  
**38 kHz Tone Generation:** Internal Crystal  
**38 kHz Tone Precision:** 38 kHz  $\pm 2$  Hz  
**Phase response:** 19/38 kHz  $0^{\circ} \pm 2^{\circ}$ , internally adjustable  
**Stereo Separation:** 30-80 Hz > 53 dB, 80 Hz-15 kHz > 60 dB  
**Crosstalk attn. (M / S):** > 40 dB, 40 Hz to 15 kHz (typ. 55 dB, 100 Hz to 8 kHz)  
**Audio Spurious Products:** > 53 kHz < 50 dB  
**THD on L & R channels:** < 0.03%, 30 Hz-15 kHz  
**Audio Filter Attenuation:** > 55 dB @ 19 kHz; > 45 dB 19 to 50 kHz; > 50 dB to 100 kHz (typ.)

### ● Audio Inputs (on rear panel)

**Baseband / Composite / MPX Input:**  
1 BNC connector, unbalanced, 2 k $\Omega$ .  
Input level range for 75 kHz Deviation: - 6 to +12 dBm, adjustable from menu  
**SCA / RDS / AUX Input:** BNC connector, unbalanced, 2 k $\Omega$ . Input level range: - 6 to +12 dBm, adjustable from menu  
**L&R or Mono Input:** 2 XLR connectors, 600 $\Omega$  balanced or unbalanced, switchable, or 10k $\Omega$  unbalanced, input level range for 75 kHz Deviation: -6 to +12 dBm, adjustable from menu  
**AES-EBU input (optional)** XLR connector and optional optical connector

### ● Other Connectors (on rear panel)

**19 kHz Output:** 1 BNC connector, unbalanced, Pilot tone 2 Vpp 19 kHz  
**Baseband / Composite / MPX Output:**  
1 BNC connector, unbalanced  
**DB25** for Analog Telemetry & Remote Control (include RF forward & reflected PWR, ext. interlock, contacts for ON/STBY & much more).  
**RJ 45s:** LAN / WEB connection, optional VOIP, optional SNMP2  
**USB A:** for SNMP2 Software  
**DB9:** RS485 for interconnection w/ other units  
**SMA**s for 10 MHz external reference port and for 1 pps port (optional).

### ● Front Panel Connectors

**USB C** or **micro:** Front panel port to access user manual file & other technical test reports  
**RF Monitor:** -36 dBc  $\pm 3$  dB, 50  $\Omega$  BNC

### ● Environmental

**Storage temperature:** -20 $^{\circ}$ C to + 60  $^{\circ}$ C  
**Operating temperature:** -10 $^{\circ}$ C to + 45 $^{\circ}$ C  
**Relative humidity:** 90% (non-condensing)  
**Max operating altitude:** 3000 m.  
**Max ambient field strength:**  $\leq 3$  V/m;  $\leq 4$  A/m  
**Cooling:** Forced air (easily replaceable fans)

### ● Physical & Electrical

**Front panel:** 483mm (19") W x 178mm (7") H (four standard rack spaces high)  
**Cabinet depth from front panel:** approximately 590 mm (23 1/4")  
**Approximate Weight:** 70 lbs (32 Kg)  
**Approx. Packed Weight:** 110 lbs (50 Kg)  
**AC Power Requirement:** 220V [ $\pm 15\%$ ] single or three phase, 50/60Hz.  
**Approx. Power Consumption @ Full PWR:** 8200 VA  
**Available Readings include:** FWD PWR, RFL PWR, Frequency, Audio Presence, Deviation, Preemphasis Status, Audio Input Selection, L & R Channels Modulation Level, Stereo Generator Enabled / Disabled, Audio Limiter Enabled / Disabled, VPA, IPA, Temperature, Efficiency, Status of FSK ID Keyer and many other readings & functions  
**All Bext products' features & specifications are subject to change without notice**